

All In One Lithium Battery Home Inverter Rechargeable 10kwh 20kwh

UN38.3,MSDS,UL,CB,BIS,PSE,GB4943.1 safety standard, CE, FCC, ROHS, battery UN38.3, MSDS, UL, CB, BIS, PSE

Basic Information

- Place of Origin:
- Brand Name: XWELL
- Certification:
- Model Number: XW-3200W
- Minimum Order Quantity: 1 pcs
- Packaging Details: Carton
- Delivery Time:
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram

7-10 working days

5000 pcs per month

China

Supply Ability:



Product Specification

 Highlight: 	lithium battery home inverter 20kwh, lithium battery home inverter 10kwh, Rechargeable 10kwh lithium battery	
Discharge Current:	100A	
Charge Current:	50A	
 Pack Voltage Output: 	48V	
• Max Power:	5.0Kw	
 Rate Energy: 	5.0Kwh	
• Rate Power:	3.2KW	
Pack Model:	LiFePO4 Battery Cell Pack	
 Capacity Options: 	100Ah 200Ah	
Working Life:	6000 Cycles	
• Wave Shape:	Pure Sine Wave Form	

All In One Rechargeable Lithium Battery Pack And 10kwh 20kwh Inverter With Inbuilt Lithium Battery

Backup Protection

Power storage brick is a battery that stores energy, detects outages and automatically becomes your home's energy source when the grid goes down. Unlike gasoline generators, Power storage brick keeps your lights on and phones charged without upkeep, fuel or noise. Pair with solar and recharge with sunlight to keep your appliances running for days.

Power Everything

Power storage brick reduces your reliance on the grid by storing your solar energy for use when there is no sun. Use Power storage brick alone or combine it with other Brightway products to save money, reduce your carbon footprint and prepare your home for power outages.

Rechargeable Lithium Battery Pack Specification

Battery Parameters			
Model	51.2V100Ah	51.2V200Ah	
Nominal voltage	51.2V		
Nominal capacity (kwh)	5KWh	10KWh	
Cell type	LiFePO4		
Cycle life	>6000 Cycles(80%DOD)		
Charge temperature range	0~65°C		
Discharge temperature range	-20~65°C		
Maximum continuous charge current	50A		
Maximum continuous discharge	100A		
current			
Color	Black /White		
Dimension (mm)	710x300x600	710x300x800	
Weight	81Kg	110Kg	
Installation method	Floor type with wheels		
Inverter Parameters			
Rated power	3.2KW		
Peak power	5KW		
Output wave form	Pure sine wave		
Input/Output AC voltage	AC 110V/220V		
Input/Output AC voltage frequency	50Hz/60Hz		

Rechargeable Lithium Battery Pack Connection Diagram



Our service

1.3 years warranty for solar lights and solar power generation system, 15 years warranty for solar panels.

- 2. Good packaging.
- 3. The main components are matched with 1% accessories.


4. In addition to customer service spare parts, customers need to take photos of damaged parts or confirm test data, and we will send damaged parts or brand new products to consumers. (Consumers who give up the opportunity to cooperate again need to bear the freight by themselves)

5. You are welcome to contact us 24 hours a day.

Company Information

We are a technological innovation company, mainly engaged in R&D and sales of lithium battery and battery pack technology, focusing on the R&D and manufacturing of new energy storage products.

In the beginning of the company establishment in 2005, we occupied 40% market share in Guangdong Province with single-





XWELL GUANGDONG XWELL TECHNOLOGY CO., LTD.

+86 18620492985 Sales@esslithiumbattery.com
 Room 322, Building 3, No. 801, Qiaoxing Avenue, Xiaoluo Village, Shatou Street, Panyu District, Guangzhou, China